

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EL2 Epoxy Laminating Resin

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Casting Resin

1.3 Details of the supplier of the safety data sheet

Company : Easy Composites Ltd
Unit 39 Park Hall Business Village,
Longton, Stoke-on-Trent, ST3 5XA

Telephone : 01782 454499
sales@easycomposites.co.uk

E-mail address

1.4 Emergency telephone number

01782 454499 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion , Category 1 H314: Causes severe skin burns and eye damage.

Serious eye damage , Category 1 H318: Causes serious eye damage.

Skin sensitisation , Category 1 H317: May cause an allergic skin reaction.

Reproductive toxicity , Category 1A H360: May damage fertility or the unborn child.

Chronic aquatic toxicity , Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : **Danger**

Hazard statements : **H314 Causes severe skin burns and eye damage.**
H317 May cause an allergic skin reaction.

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

Precautionary statements	H360	May damage fertility or the unborn child.
	H411	Toxic to aquatic life with long lasting effects.
: Prevention:	P201	Obtain special instructions before use.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
: Response:	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
	P308 + P313	IF exposed or concerned: Get medical advice/ attention.

Hazardous components which must be listed on the label:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700)

1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with (chloromethyl)oxirane

Bisphenol-F-epichlorohydrin resin, MM=<700

oxirane, mono[(C12-14-alkyloxy)methyl]derivs

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Modified epoxy resin

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight	25068-38-6 01-2119456619-26	Eye Irrit.2; H319 Skin Irrit.2; H315 Skin Sens.1; H317	>= 50 - <= 100

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

=< 700)		Aquatic Chronic2; H411	
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with (chloromethyl)oxirane	30499-70-8	Skin Corr.1; H314 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Chronic2; H411 Repr.1; H360	>= 12,5 - < 20
Bisphenol-F-epichlorohydrin resin, MM=<700	9003-36-5 01-2119454392-40	Skin Irrit.2; H315 Eye Irrit.2; H319 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 10 - < 12,5
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	Not Assigned 271-846-8 01-2119485289-22	Skin Irrit.2; H315 Skin Sens.1; H317	>= 3 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Keep warm and in a quiet place.
Show this safety data sheet to the doctor in attendance.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Do NOT use solvents or thinners.
If on clothes, remove clothes.
If skin irritation persists, call a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
If easy to do, remove contact lens, if worn.
- If swallowed : Keep at rest.
Do not induce vomiting without medical advice.
Keep respiratory tract clear.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : irritant effects
Redness

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam
Sand
Carbon dioxide (CO₂)
Water mist

Unsuitable extinguishing media : Water spray jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Immediately evacuate personnel to safe areas.
Prevent fire extinguishing water from contaminating surface water or the ground water system.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

environment.

Try to prevent the material from entering drains or water courses.

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms. Avoid inhalation, ingestion and contact with skin and eyes. Wear personal protective equipment.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers.
- Advice on common storage : Keep away from oxidizing agents, strongly acid or alkaline materials and amines.
Keep product and empty container away from heat and sources of ignition.
Keep away from food and drink.
- Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight =< 700)	: End Use: Workers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term systemic effects Value: 8,33 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects, Long-term local effects Value: 12,25 mg/m3 End Use: Consumers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term systemic effects Value: 3,571 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Acute systemic effects, Long-term systemic effects Value: 0,75 mg/kg
oxirane, mono[(C12-14- alkyloxy)methyl]derivs	: End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 3,9 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 13,8 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight =< 700)	: Fresh water Value: 0,006 mg/l Marine water Value: 0,0006 mg/l Intermittent releases Value: 0,018 mg/l Sewage treatment plant Value: 10 mg/l Fresh water sediment Value: 0,996 mg/kg Marine sediment Value: 0,0996 mg/kg Soil Value: 0,196 mg/kg
oxirane, mono[(C12-14- alkyloxy)methyl]derivs	: Sewage treatment plant Value: 10 mg/l

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

Fresh water
Value: 0,0072 mg/l
Marine water
Value: 0,00072 mg/l
Fresh water sediment
Value: 66,77 mg/kg
Marine sediment
Value: 6,677 mg/kg
Soil
Value: 80,12 mg/kg

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system
effective ventilation in all processing areas

Personal protective equipment

- Eye protection : Do not wear contact lenses.
Safety glasses with side-shields conforming to EN166
Ensure that eyewash stations and safety showers are close to the workstation location.
- Hand protection
Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.
- Skin and body protection : Protective suit
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In the case of vapour formation use a respirator with an approved filter.
Respirator with a vapour filter (EN 141)
Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
- Protective measures : Avoid contact with skin.
Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : light yellow
- Odour : slight
- Odour Threshold : not determined

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

pH	: not determined
Melting point/freezing point	: Not applicable
Boiling point/boiling range	: > 200 °C
Flash point	: 150 °C
Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: 1,15 g/cm ³ (25 °C)
Bulk density	: not determined
Solubility(ies) Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: Not applicable
Thermal decomposition	: Method: No data available
Viscosity Viscosity, dynamic	: 1.200 - 1.800 mPa.s (25 °C)
Viscosity, kinematic	: not determined
Explosive properties	: Not applicable
Oxidizing properties	: Not applicable

9.2 Other information

Surface tension	: not determined
Sublimation point	: Not applicable

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:
Bases
Strong oxidizing agents
Avoid amines.

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

Hazardous decomposition products : This product may release the following:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =<= 700):

Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Method: OECD Test Guideline 420
GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation

Product:

Remarks: No data available

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: Skin irritation
GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Test Type: Mouse Local Lymph Node assay (LLNA)
Species: Mouse
Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact.
GLP: yes

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

Product:

Remarks: Not applicable

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 1,7 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight =< 700):

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.
Container hazardous when empty.
Do not dispose of with domestic refuse.
Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID/ADN : UN 1760

IMDG : UN 1760

IATA : UN 1760

14.2 UN proper shipping name

ADR/RID/ADN : CORROSIVE LIQUID, N.O.S.
(Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl, Epoxy resin)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

- IMDG** : CORROSIVE LIQUID, N.O.S.
(Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl, Epoxy resin)
- IATA** : Corrosive liquid, n.o.s.
(Reaction mass of 1-(2,3-epoxypropoxy)-2,2-bis ((2,3-epoxypropoxy)methyl) butane and 1-(2,3-epoxypropoxy)-2-((2,3-epoxypropoxy)methyl, Epoxy resin)

14.3 Transport hazard class(es)

- ADR/RID/ADN** : 8
- IMDG** : 8
- IATA** : 8

14.4 Packing group

- ADR/RID/ADN**
- Packing group : III
- Classification Code : C9
- Hazard Identification Number : 80
- Labels : 8
- Tunnel restriction code : E
- IMDG**
- Packing group : III
- Labels : 8
- EmS Code : F-A, S-B
- IATA**
- Packing instruction (cargo aircraft) : 856
- Packing instruction (passenger aircraft) : 852
- Packing group : III
- Labels : 8

14.5 Environmental hazards

- ADR/RID/ADN**
- Environmentally hazardous : yes
- IMDG**
- Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable
- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

- H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H360 : May damage fertility or the unborn child.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

- Aquatic Chronic : Chronic aquatic toxicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

Further information

- Training advice : Provide adequate information, instruction and training for operators.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

EL2 Epoxy Laminating Resin

Version 4.0 SDB_GB

Revision Date 29.03.2017

Print Date 04.04.2017

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AT30 Slow Hardener

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy Hardener

1.3 Details of the supplier of the safety data sheet

Company : Easy Composites Ltd
Unit 39 Park Hall Business Village,
Longton, Stoke-on-Trent, ST3 5XA

Telephone : 01782 454499

E-mail address : sales@easycomposites.co.uk

1.4 Emergency telephone number

01782 4544 499 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity , Category 4	H302: Harmful if swallowed.
Skin corrosion , Category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage , Category 1	H318: Causes serious eye damage.
Skin sensitisation , Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity , Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H302

Harmful if swallowed.

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Precautionary statements	H314	Causes severe skin burns and eye damage.
	H317	May cause an allergic skin reaction.
	H412	Harmful to aquatic life with long lasting effects.
	Prevention:	
	P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	Response:	
	P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304 + P340 + P310	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
	P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-

3-aminomethyl-3,5,5-trimethylcyclohexylamine

trimethylhexane-1,6-diamine

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Cycloaliphatic amine based mixture

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-	9046-10-0	Skin Corr.1C; H314 Eye Dam.1; H318 Aquatic Chronic3; H412	>= 30 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32	Acute Tox.4; H312 Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	$\geq 30 - < 50$
trimethylhexane-1,6-diamine	25620-58-0 247-134-8	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	$\geq 7 - < 10$
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	$\geq 1 - < 3$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.
Keep warm and in a quiet place.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Do NOT use solvents or thinners.
If on clothes, remove clothes.
Burns must be treated by a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,
for at least 15 minutes.
If eye irritation persists, consult a specialist.
If easy to do, remove contact lens, if worn.
- If swallowed : Do NOT induce vomiting.
If a person vomits when lying on his back, place him in the recovery position.
Call a physician immediately.
Give small amounts of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Burn
superficial burning sensation
Redness

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Severe irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)
Foam
Dry powder
Water mist

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.
Cool closed containers exposed to fire with water spray.
Hazardous decomposition products formed under fire conditions.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Immediately evacuate personnel to safe areas.
Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

environment.
Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours or spray mist.
Avoid inhalation, ingestion and contact with skin and eyes.
Wear personal protective equipment.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

Further information on storage conditions : Protect from moisture.

Advice on common storage : Keep away from isocyanates.
Do not store near acids.
Keep away from oxidizing agents.

Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-	: End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 2,5 mg/kg End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term local effects Value: 0,623 mg/cm2 End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 1,25 mg/kg End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term local effects Value: 0,311 mg/cm2 End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 0,04 mg/kg
benzyl alcohol	: End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term exposure, Systemic effects Value: 450 mg/m3 End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term exposure, Systemic effects Value: 90 mg/m3 End Use: Workers Exposure routes: Skin contact Potential health effects: Short-term exposure, Systemic effects Value: 47 mg/kg End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term exposure, Systemic effects Value: 9,5 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Short-term exposure, Systemic effects Value: 25 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term exposure, Systemic effects Value: 5 mg/kg End Use: Consumers

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Exposure routes: Inhalation
Potential health effects: Short-term exposure, Systemic effects
Value: 40,55 mg/m³
End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term exposure, Systemic effects
Value: 8,11 mg/m³
End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Short-term exposure, Systemic effects
Value: 28,5 mg/kg
End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Long-term exposure, Systemic effects
Value: 5,7 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-	: Fresh water
	Value: 0,015 mg/l
	Marine water
	Value: 0,0143 mg/l
	Fresh water sediment
	Value: 0,132 mg/kg
	Marine sediment
	Value: 0,125 mg/kg
	Soil
	Value: 0,0176 mg/kg
3-aminomethyl-3,5,5-trimethylcyclohexylamine	: Fresh water
	Value: 0,06 mg/l
	Marine water
	Value: 0,006 mg/l
	Intermittent releases
	Value: 0,23 mg/l
	Fresh water sediment
	Value: 5,784 mg/kg
	Marine sediment
	Value: 0,578 mg/kg
benzyl alcohol	: Fresh water
	Value: 1 mg/l
	Marine water
	Value: 0,1 mg/l
	Fresh water sediment
	Value: 5,27 mg/kg
	Marine sediment
	Value: 0,527 mg/kg
	Soil
	Value: 1,121 mg/kg

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Value: 0,456 mg/kg
Sewage treatment plant
Value: 39 mg/l
Intermittent releases
Value: 2,3 mg/l

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system
effective ventilation in all processing areas

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Do not wear contact lenses.
Ensure that eyewash stations and safety showers are close to the workstation location.
- Hand protection
Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.
- Skin and body protection : Protective suit
- Respiratory protection : Use respirator when performing operations involving potential exposure to vapour of the product.
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Respirator with a vapour filter (EN 141)
- Protective measures : Avoid contact with skin.
Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : light yellow
- Odour : ammoniacal
- Odour Threshold : not determined
- pH : not determined
- Melting point/freezing point : Not applicable
- Boiling point/boiling range : > 150 °C
- Flash point : 150 °C

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: 0,93 g/cm ³ (25 °C)
Bulk density	: not determined
Solubility(ies) Solubility in other solvents	: not determined
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: Not applicable
Thermal decomposition	: Method: No data available
Viscosity Viscosity, dynamic	: 5 - 20 mPa.s (25 °C)
Viscosity, kinematic	: not determined
Explosive properties	: Not applicable
Oxidizing properties	: Not applicable

9.2 Other information

Surface tension	: not determined
Sublimation point	: Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Acids
Strong oxidizing agents

10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : This product may release the following:
Nitrogen oxides (NOx)
Carbon monoxide
Carbon dioxide (CO2)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 909,09 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Acute oral toxicity : LD50 (Rat, male and female): 2.885,3 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): 2.979,7 mg/kg
Method: OECD Test Guideline 402
GLP: yes

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate

benzyl alcohol:

Acute inhalation toxicity : LC50 (Rat, male and female): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Method: OECD Test Guideline 403

GLP: yes

Skin corrosion/irritation

Product:

Remarks: Acute dermal irritation/corrosion

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive

benzyl alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Method: OECD Test Guideline 405

Result: Risk of serious damage to eyes.

benzyl alcohol:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

GLP: yes

Respiratory or skin sensitisation

Product:

Remarks: No data available

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 15 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 80 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 0,32

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

- Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: Directive 67/548/EEC, Annex V, C.1.
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes
- Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)): > 50 mg/l
Exposure time: 72 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.3.
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
GLP: yes

benzyl alcohol:

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes
- Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Biodegradability : Test Type: aerobic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Result: Not readily biodegradable.
Method: OECD Test Guideline 301B
GLP: yes

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : Test Type: aerobic
Result: Not readily biodegradable.
Method: Directive 67/548/EEC Annex V, C.4.A.
GLP: yes

trimethylhexane-1,6-diamine:

Biodegradability : Test Type: aerobic
Result: Not readily biodegradable.
Method: Directive 67/548/EEC Annex V, C.4.A.
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-omega.-(2-aminomethylethoxy)-:

Partition coefficient: n-octanol/water : log Pow: 1,34 (25 °C)
Method: OECD Test Guideline 117
GLP: yes

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n-octanol/water : log Pow: 0,99
Method: OECD Test Guideline 107
GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : In accordance with local and national regulations.
Container hazardous when empty.
Do not dispose of with domestic refuse.
Do not mix waste streams during collection.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

- ADR/RID/ADN : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

- ADR/RID/ADN : AMINES, LIQUID, CORROSIVE, N.O.S.
(Polyoxypropylene Diamine)
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(Polyoxypropylene Diamine)
IATA : Amines, liquid, corrosive, n.o.s.
(Polyoxypropylene Diamine)

14.3 Transport hazard class(es)

- ADR/RID/ADN : 8
IMDG : 8
IATA : 8

14.4 Packing group

- ADR/RID/ADN
Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
- IMDG
Packing group : III
Labels : 8
EmS Code : F-A, S-B
Remarks : IMDG Code segregation group 18 - Alkalies
- IATA
Packing instruction (cargo aircraft) : 856
Packing instruction : 852

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

(passenger aircraft)

Packing group : III

Labels : 8

14.5 Environmental hazards

ADR/RID/ADN

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H412 : Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 Slow Hardener

Version 4.0 SDB_GB

Revision Date 15.12.2016

Print Date 20.12.2016

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation

Further information

Training advice	: Provide adequate information, instruction and training for operators.
-----------------	---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : AT30 FAST Epoxy Hardener

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy Hardener

1.3 Details of the supplier of the safety data sheet

Company : Easy Composites Ltd
Unit 39 Park Hall Business Village,
Longton, Stoke-on-Trent, ST3 5XA

Telephone : 01782 454 499
Telefax :
E-mail address : sales@easycomposites.co.uk

1.4 Emergency telephone number

01782 454 499 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity , Category 4	H302: Harmful if swallowed.
Skin corrosion , Category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage , Category 1	H318: Causes serious eye damage.
Skin sensitisation , Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure , Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Chronic aquatic toxicity , Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Hazard statements	: H302 H314 H317 H373 H411	Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	: EUH071	Corrosive to the respiratory tract.
Precautionary statements	: Prevention: P260 P273 P280 Response: P303 + P361 + P353 P304 + P340 + P310 P305 + P351 + P338 + P310	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-methylenebis(cyclohexylamine)

m-phenylenebis(methylamine)

3,6,9,12-tetra-azatetradecamethylenediamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5

3,6,9-triazaundecamethylenediamine

3,3'-ethylenedioxybis(propylamine)

3-aminopropyltriethoxysilane

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Cycloaliphatic and aliphatic amine based mixture

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32	Acute Tox.4; H312 Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 20 - < 25
4,4'-methylenebis(cyclohexylamine)	1761-71-3 217-168-8	Acute Tox.4; H302 Skin Corr.1A; H314 Skin Sens.1; H317 STOT RE2; H373	>= 20 - < 25
m-phenylenebis(methylamine)	1477-55-0 216-032-5 01-2119480150-50	Acute Tox.4; H302 Acute Tox.4; H332 Skin Corr.1B; H314 Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 20 - < 25
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38	Acute Tox.4; H302 Acute Tox.4; H332 Eye Irrit.2; H319	>= 12,5 - < 20
3,6,9,12-tetra-azatetradecamethylenediamine	4067-16-7 223-775-9	Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410 Acute Tox.4; H302 Acute Tox.4; H312	>= 7 - < 10
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5	38294-64-3	Acute Tox.4; H302 Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Chronic3; H412	>= 1 - < 2,5
3,6,9-triazaundecamethylenediamine	112-57-2 203-986-2 /	Acute Tox.4; H312 Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317	>= 1 - < 2,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

		Aquatic Chronic2; H411	
3,3'-ethylenedioxybis(propylamine)	2997-01-5 221-067-4	Acute Tox.4; H312 Skin Corr.1B; H314 Skin Sens.1; H317	$\geq 1 - < 3$
3-aminopropyltriethoxysilane	919-30-2 213-048-4 01-2119480479-24	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1; H317	$\geq 0,25 - < 0,5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Show this safety data sheet to the doctor in attendance.
Keep warm and in a quiet place.
Take off all contaminated clothing immediately.
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Do NOT use solvents or thinners.
If on clothes, remove clothes.
Burns must be treated by a physician.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,
for at least 15 minutes.
If eye irritation persists, consult a specialist.
If easy to do, remove contact lens, if worn.
- If swallowed : Do NOT induce vomiting.
If a person vomits when lying on his back, place him in the recovery position.
Call a physician immediately.
Give small amounts of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Burn
superficial burning sensation
Redness
Severe irritation

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation

AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

with the doctor responsible for industrial medicine.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)
Foam
Dry powder
Water mist

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.
Cool closed containers exposed to fire with water spray.
Hazardous decomposition products formed under fire conditions.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Immediately evacuate personnel to safe areas.
Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Pick up and transfer to properly labelled containers.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours or spray mist.
Avoid inhalation, ingestion and contact with skin and eyes.
Wear personal protective equipment.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.
- Further information on storage conditions : Protect from moisture.
- Advice on common storage : Keep away from isocyanates.
Do not store near acids.
Keep away from oxidizing agents.
- Other data : Stable at normal ambient temperature and pressure.

7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

benzyl alcohol	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term exposure, Systemic effects Value: 450 mg/m ³ End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term exposure, Systemic effects Value: 90 mg/m ³ End Use: Workers Exposure routes: Skin contact Potential health effects: Short-term exposure, Systemic effects Value: 47 mg/kg End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term exposure, Systemic effects Value: 9,5 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Short-term exposure, Systemic effects Value: 25 mg/kg End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term exposure, Systemic effects Value: 5 mg/kg End Use: Consumers Exposure routes: Inhalation Potential health effects: Short-term exposure, Systemic effects Value: 40,55 mg/m ³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term exposure, Systemic effects Value: 8,11 mg/m ³ End Use: Consumers Exposure routes: Skin contact Potential health effects: Short-term exposure, Systemic effects Value: 28,5 mg/kg End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term exposure, Systemic effects Value: 5,7 mg/kg
3-aminopropyltriethoxysilane	:	End Use: Workers Exposure routes: Skin contact Potential health effects: Acute systemic effects, Long-term systemic effects Value: 8,3 mg/kg End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects, Long-term

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

systemic effects
Value: 59 mg/m³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

3-aminomethyl-3,5,5-trimethylcyclohexylamine	: Fresh water Value: 0,06 mg/l Marine water Value: 0,006 mg/l Intermittent releases Value: 0,23 mg/l Fresh water sediment Value: 5,784 mg/kg Marine sediment Value: 0,578 mg/kg Sewage treatment plant Value: 3,18 mg/l Soil Value: 1,121 mg/kg
benzyl alcohol	: Fresh water Value: 1 mg/l Marine water Value: 0,1 mg/l Fresh water sediment Value: 5,27 mg/kg Marine sediment Value: 0,527 mg/kg Soil Value: 0,456 mg/kg Sewage treatment plant Value: 39 mg/l Intermittent releases Value: 2,3 mg/l
3-aminopropyltriethoxysilane	: Fresh water Value: 0,33 mg/l Marine water Value: 0,033 mg/l Intermittent releases Value: 3,3 mg/l Fresh water sediment Value: 0,26 mg/kg Soil Value: 0,04 mg/kg Sewage treatment plant Value: 13 mg/l

8.2 Exposure controls

Engineering measures

Effective exhaust ventilation system
effective ventilation in all processing areas

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Do not wear contact lenses.
Ensure that eyewash stations and safety showers are close to the workstation location.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Hand protection	
Material	: Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.
Skin and body protection	: Protective suit
Respiratory protection	: Use respirator when performing operations involving potential exposure to vapour of the product. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used. Respirator with a vapour filter (EN 141)
Protective measures	: Avoid contact with skin. Wear suitable protective equipment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: light yellow
Odour	: ammoniacal
Odour Threshold	: not determined
pH	: not determined
Melting point/freezing point	: Not applicable
Boiling point/boiling range	: > 150 °C
Flash point	: 100 °C
Evaporation rate	: not determined
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density	: not determined
Density	: 1,04 g/cm ³ (25 °C)
Bulk density	: not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Solubility(ies)	
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: Not applicable
Thermal decomposition	: Method: No data available
Viscosity	
Viscosity, dynamic	: 30 - 80 mPa.s (25 °C)
Viscosity, kinematic	: not determined
Explosive properties	: Not applicable
Oxidizing properties	: Not applicable

9.2 Other information

Surface tension	: not determined
Sublimation point	: Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	: Reacts with the following substances: Acids Strong oxidizing agents
---------------------	---

10.4 Conditions to avoid

Conditions to avoid	: No decomposition if used as directed.
---------------------	---

10.5 Incompatible materials

Materials to avoid	: Strong acids Strong oxidizing agents
--------------------	---

10.6 Hazardous decomposition products

Hazardous decomposition products	: This product may release the following: Nitrogen oxides (NOx) Carbon monoxide
----------------------------------	---

AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Carbon dioxide (CO₂)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 537,56 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg
Method: Calculation method

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate

benzyl alcohol:

Acute inhalation toxicity : LC50 (Rat, male and female): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes

3,6,9-triazaundecamethylenediamine:

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg
Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Product:

Remarks: Acute dermal irritation/corrosion

Components:

benzyl alcohol:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

GLP: yes

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Components:

benzyl alcohol:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

GLP: yes

Respiratory or skin sensitisation

Product:

Remarks: No data available

Components:

3-aminopropyltriethoxysilane:

Test Type: Buehler Test

Exposure routes: Dermal

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

GLP: yes

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

STOT - single exposure

STOT - repeated exposure

Repeated dose toxicity

Product:

Remarks: No data available

Aspiration toxicity

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

No aspiration toxicity classification

Further information

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: Directive 67/548/EEC, Annex V, C.1.
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)): > 50 mg/l
Exposure time: 72 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.3.
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
GLP: yes

benzyl alcohol:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

3-aminopropyltriethoxysilane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 934 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 331 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes
- Toxicity to algae : EC50 (Scenedesmus subspicatus): > 1.000 mg/l
Exposure time: 72 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.3.
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : Test Type: aerobic
Result: Not readily biodegradable.
Method: Directive 67/548/EEC Annex V, C.4.A.
GLP: yes

3-aminopropyltriethoxysilane:

Biodegradability : Test Type: aerobic
Result: Not readily biodegradable.
Method: Directive 67/548/EEC Annex V, C.4.A.
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: n-octanol/water : log Pow: 0,99
Method: OECD Test Guideline 107
GLP: yes

12.4 Mobility in soil

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with local and national regulations.
Container hazardous when empty.
Do not dispose of with domestic refuse.
Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR/RID/ADN : UN 2735
IMDG : UN 2735
IATA : UN 2735

14.2 UN proper shipping name

ADR/RID/ADN : AMINES, LIQUID, CORROSIVE, N.O.S.
(Cyclohexanamine, 4,4'-methylenebis, m-Phenylenebis(methylamine))
IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.
(Cyclohexanamine, 4,4'-methylenebis, m-Phenylenebis(methylamine))
IATA : Amines, liquid, corrosive, n.o.s.
(Cyclohexanamine, 4,4'-methylenebis, m-Phenylenebis(methylamine))

14.3 Transport hazard class(es)

ADR/RID/ADN : 8
IMDG : 8

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

IATA : 8

14.4 Packing group

ADR/RID/ADN

Packing group : III
Classification Code : C7
Hazard Identification Number : 80
Labels : 8
Remarks : ADR: These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

IMDG

Packing group : III
Labels : 8
EmS Code : F-A, S-B
Remarks : IMDG: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provisions of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class all provisions of this Code relevant to any additional hazards continue to apply.

IMDG Code segregation group 18 - Alkalis

IATA

Packing instruction (cargo aircraft) : 856
Packing instruction (passenger aircraft) : 852
Packing group : III
Labels : 8
Remarks : IATA: These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

14.5 Environmental hazards

ADR/RID/ADN

Environmentally hazardous : yes

IMDG

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Marine pollutant : yes

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : ethanol

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t

15.2 Chemical safety assessment

Not applicable

SECTION 16: Other information

Full text of H-Statements

H302 : Harmful if swallowed.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



AT30 FAST Epoxy Hardener

Version 2.0 SDB_GB

Revision Date 18.10.2016

Print Date 21.10.2016

Aquatic Acute	: Acute aquatic toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure

Further information

Training advice	: Provide adequate information, instruction and training for operators.
-----------------	---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.