



## SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 1

Compilation date: 08/10/2015

Revision date: 16/03/2017

Revision No: 6

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** EMP160 High Temp Epoxy Moulding Paste  
**Product code:** EMP160

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom  
**Tel:** +44 (0) 1782 454499  
**Fax:** +44 (0) 1782 596868  
**Email:** sales@easycomposites.co.uk

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1782 454499  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark  
GHS09: Environmental



**Signal words:** Warning

**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P264: Wash hands thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see instructions on this label).

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 3

## BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-25%

## N,N,N',N'-TETRAGLYCIDYL-4,4'-DIAMINO DIPHENYL METHANE

249-204-3	28768-32-3	-	Aquatic Chronic 2: H411; Skin Sens. 1: H317	1-25%
-----------	------------	---	--	-------

## 1,4-BIS(2,3-EPOXYPROPOXY) BUTANE

219-371-7	2425-79-8	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	1-25%
-----------	-----------	---	---	-------

## N,N-DIGLYCIDYL ANILINE

-	2095-06-9	-	Acute Tox. 4: H302; Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; STOT SE 3: H335	1-25%
---	-----------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Water spray. Water fog. Dry chemical powder. Carbon dioxide. Alcohol or polymer foam. Alcohol resistant foam.

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 4

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 5

**Eye protection:** Safety glasses.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Grey

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Viscosity:** Not applicable.

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 1.20 - 1.30

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Polymerisation may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Amines.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 6

## 11.1. Information on toxicological effects

### Hazardous ingredients:

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

#### N,N,N',N'-TETRAGLYCIDYL-4,4'-DIAMINO DIPHENYL METHANE

DERMAL	RBT	LD50	>3000	mg/kg
DUST/MIST	RAT	4H LC50	>30	mg/m3
ORAL	MUS	LD50	>5000	mg/kg

#### 1,4-BIS(2,3-EPOXYPROPOXY) BUTANE

ORL	RAT	LD50	1134	mg/kg
-----	-----	------	------	-------

#### N,N-DIGLYCIDYL ANILINE

DERMAL	RBT	LD50	3560	mg/kg
ORAL	RAT	LD50	>1620	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 7

## Hazardous ingredients:

### N,N,N',N'-TETRAGLYCIDYL-4,4'-DIAMINO DIPHENYL METHANE

AQUATIC PLANT	96H ErC50	38.234	mg/l
CRUSTACEA	48h LC50	14.682	mg/l
FISH	96H LC50	2.454	mg/l

## 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

## 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

## 12.4. Mobility in soil

**Mobility:** No data available.

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3077

### 14.2. UN proper shipping name

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(Epoxy resin)

### 14.3. Transport hazard class(es)

**Transport class:** 9

### 14.4. Packing group

**Packing group:** III

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy Moulding Paste

Page: 8

## 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

## 14.6. Special precautions for user

Tunnel code: E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** EMP160 High Temp Epoxy Moulding Paste Hardener

**Product code:** EMP160

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Easy Composites Ltd  
Unit 39, Park Hall Business Village  
Longton, Stoke on Trent  
Staffordshire  
ST3 5XA  
United Kingdom

**Tel:** +44 (0) 1782 454499

**Fax:** +44 (0) 1782 596868

**Email:** sales@easycomposites.co.uk

# SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1782 454499  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Acute Tox. 4: H302; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317

**Most important adverse effects:** Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H302: Harmful if swallowed.  
H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.  
H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS05: Corrosion  
GHS07: Exclamation mark



**Signal words:** Danger

**Precautionary statements:** P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.  
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P362+P364: Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE) - REACH registered number(s): 01-2119480150-50

EINECS	CAS	PBT / WEL	CLP Classification	Percent
--------	-----	-----------	--------------------	---------

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 3

216-032-5	1477-55-0	-	Acute Tox. 4: H302+H332; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412; -: EUH071	25-50%
-----------	-----------	---	--	--------

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE - REACH registered number(s): 01-2119514687-32

220-666-8	2855-13-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	25-50%
-----------	-----------	---	--	--------

PHENOL, STYRENATED - REACH registered number(s): 01-2119980970-27

262-975-0	61788-44-1	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-25%
-----------	------------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

### 4.2. Most important symptoms and effects, both acute and delayed

- Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
- Eye contact:** Corneal burns may occur. May cause permanent damage.
- Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 4

## 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 5

## 8.1. Control parameters

**Workplace exposure limits:** No data available.

## DNEL/PNEC Values

**Hazardous ingredients:**

### M-PHENYLENEBIS(METHYLAMINE)

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	1.2mg/m <sup>3</sup>	Workers	Chronic - Systemic effects
DNEL	Inhalation	0.2mg/m <sup>3</sup>	Workers	Chronic - Local effects
DNEL	Dermal	0.33mg/kg bw/day	Workers	Chronic - Systemic effects
PNEC	Fresh water	0.094 mg/l	-	-
PNEC	Marine water	0.009mg/l	-	-
PNEC	water	0.152mg/l	-	-
PNEC	Microorganisms in sewage treatment	10mg/l	-	-
PNEC	Fresh water sediments	0.43mg/kg	-	-
PNEC	Marine sediments	0.043mg/kg	-	-
PNEC	Soil (agricultural)	0.045mg/kg	-	-

### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	20.1 mg/m <sup>3</sup>	Workers	-
PNEC	Fresh water	0.06 mg/l	-	-
PNEC	Marine water	0.006 mg/l	-	-
PNEC	Fresh water sediments	5.784 mg/kg	-	-
PNEC	Marine sediments	0.578 mg/kg1.121 mg/	-	-
PNEC	Soil (agricultural)	-	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Environmental:** The floor of the storage room must be impermeable to prevent the escape of liquids.

## Section 9: Physical and chemical properties

[cont...]

# SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 6

## 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale yellow

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Viscosity:** 15 mPas (25°C)

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 0.95 - 1.00

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

## SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 7

### Hazardous ingredients:

#### M-PHENYLENEBIS(METHYLAMINE)

DERMAL	RAT	LD50	>3100	mg/kg
DUST/MIST	RAT	4H LC50	1.34	mg/l
ORAL	MUS	LD50	1180	mg/kg

#### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

DERMAL	RAT	LD50	> 2000	mg/kg
DERMAL	RBT	LD50	1840	mg/kg
DUST/MIST	RAT	4H LC50	> 5.01	mg/l
ORAL	RAT	LD50	1030	mg/kg

#### PHENOL, STYRENATED

DERMAL	RAT	LD50	>2000	mg/kg
DUST/MIST	RAT	4H LC0	4.9	mg/l
ORAL	RAT	LD50	>2000	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

**Eye contact:** Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

[cont...]

## SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 8

### Hazardous ingredients:

#### M-PHENYLENEBIS(METHYLAMINE)

ALGAE	72H EC50	20.3	mg/l
ALGAE	72H NOEC	10.5	mg/l
ALGAE (pseudokirchneriella subcapitata)	72H ErC50	33.3	mg/l
Daphnia magna	21D LC50	6.77	mg/l
Daphnia magna	21D NOEC	4.7	mg/l
Daphnia magna	24H EC0	16	mg/l
Daphnia magna	24H EC50	35.1	mg/l
Daphnia magna	48H EC0	8.9	mg/l
Daphnia magna	48H EC50	15.2	mg/l
Oryzias latipes	96H LC50	87.6	mg/l

#### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

BACTERIA	15H EC10	1120	mg/l
Daphnia magna	48H EC50	23	mg/l
Scenedesmus Subspicatus	72H EC50	> 50	mg/l
ZEBRAFISH (Brachydanio rerio)	96H LC50	110	mg/l

#### PHENOL, STYRENATED

ALGAE (Scenedesmus sp.)	72H EL50	3.14	mg/l
Daphnia magna	48H EL50	1 - 10	mg/l
Daphnia magna	NOEC (21d)	0.115	mg/l
FISH	96H LL50	14.8	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

[cont...]



# SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 9

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN2735

### 14.2. UN proper shipping name

**Shipping name:** POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
(Contains: Aliphatic Amines)

### 14.3. Transport hazard class(es)

**Transport class:** 8

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH071: Corrosive to the respiratory tract.

[cont...]

## SAFETY DATA SHEET

EMP160 High Temp Epoxy  
Moulding Paste Hardener

Page: 10

H302: Harmful if swallowed.

H302+H332: Harmful if swallowed or if inhaled

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.